Composites, vol. 45, no. 1, pp. 722–737, Oct. 2023, doi:10.1002/pc.27810.

[29] A. Karimi, D. Rahmatabadi, and M. Baghani, “Various FDM Mechanisms Used in the Fabrication of Continuous-Fiber Reinforced Composites: A Review,” *Polymers*, vol. 16, no. 6, p. 831, Mar. 2024, doi: 10.3390/polym16060831.

[30] Z. An, X. Cheng, D. Zhao, Y. Ma, X. Guo, and Y. Cheng, “Tensile and Compressive Properties of Woven Fabric Carbon Fiber-Reinforced Polymer Laminates Containing Three-Dimensional Microvascular Channels,” *Polymers*, vol. 16, no. 5, p. 665, Feb. 2024, doi:10.3390/polym16050665.

[31] R. Amara, B. Riadh, A. A. Hassen, N. Mokhtar, and L. Hadji, “Hygrothermal effect of bio-inspired helicoid laminate plate for strengthening damaged RC beam,” *Mechanics of Advanced Materials and Structures*, pp. 1–18, Aug. 2024, doi:10.1080/15376494.2024.2392623.

[32] C. J. Jenkins, M. J. Donough, and G. B. Prusty, “Design and manufacture of mould-free fibre-reinforced laminates with compound curvature,” *The International Journal of Advanced Manufacturing Technology*, vol. 131, no. 3–4, pp. 1795–1806, Feb. 2024, doi:10.1007/s00170-024-13226-2.