















- doi:10.1016/j.tws.2021.107903.
- [12] S. Shirzadian, S. Bhowmick, and A. T. Alpas, "Characterization of galling during dry and lubricated punching of AA5754 sheet," *Adv. Ind. Manuf. Eng.*, vol. 3, p. 100064, 2021, doi:10.1016/j.aime.2021.100064.
- [13] J. Wang *et al.*, "A self-piercing riveting method for joining of continuous carbon fiber reinforced composite and aluminum alloy sheets," *Compos. Struct.*, vol. 259, no. September 2020, p. 113219, 2021, doi: 10.1016/j.compstruct.2020.113219.
- [14] H. Zhao, L. Han, Y. Liu, and X. Liu, "Analysis of joint formation mechanisms for self-piercing riveting (SPR) process with varying joining parameters," *J. Manuf. Process.*, vol. 73, no. September 2021, pp. 668–685, 2022, doi: 10.1016/j.jmapro.2021.11.038.
- [15] G. Huang, T. Yang, Z. He, L. Yu, and H. Xiao, "Polyurethane as a modifier for road asphalt: A literature review," *Constr. Build. Mater.*, vol. 356, no. June, 2022, doi: 10.1016/j.conbuildmat.2022.129058.
- [16] P. Y. Le Gac, P. A. Albouy, B. Fayolle, and J. Verdu, "Relationship between macromolecular network and fatigue properties of unfilled polychloroprene rubber," *Polym. Degrad. Stab.*, vol. 192, p. 109669, 2021, doi: 10.1016/j.polymdegradstab.2021.109669.
- [17] S. Sharma, P. Sudhakara, S. K. Misra, and J. Singh, "A comprehensive review of current developments on the waste-reinforced polymer-matrix composites for automotive, sports goods and construction applications: Materials, processes and properties," *Mater. Today Proc.*, vol. 33, pp. 1671–1679, 2019, doi:10.1016/j.matpr.2020.06.523.
- [18] P. Herrera, E. Hernandez-Nava, R. Thornton, and T. Slatter, "Abrasive wear resistance of Ti-6AL-4V obtained by the conventional manufacturing process and by electron beam melting (EBM)," *Wear*, vol. 524–525, no. April, 2023, doi: 10.1016/j.wear.2023.204879.
- [19] N. Mandlekar, M. Joshi, and B. S. Butola, "A review on specialty elastomers based potential inflatable structures and applications," *Adv. Ind. Eng. Polym. Res.*, vol. 5, no. 1, pp. 33–45, 2022, doi:10.1016/j.aiepr.2021.05.004.
- [20] I. Hossain, M. T. Islam, M. Samsuzzaman, H. Alsaif, H. Rmili, and M. S. Soliman, "Dielectric characterization of Mg–Zn ferrite-based high permittivity flexible substrate for SNG metamaterial," *J. Mater. Res. Technol.*, vol. 24, pp. 879–894, 2023, doi: 10.1016/j.jmrt.2023.03.058.
- [21] P. Esmailpour, A. Mamazizi, and G. S. P. Madabhushi, "An overview of the model container types in physical modeling of geotechnical problems," *Soil Dyn. Earthq. Eng.*, vol. 168, no. July 2022, p. 107827, 2023, doi: 10.1016/j.soildyn.2023.107827.
- [22] F. Zuhdi and R. S. Anggraini, "The Indonesian Natural Rubber Export Competitiveness in Global Market," *Int. J. Agric. Syst.*, vol. 8, no. 2, pp. 130–139, 2020, doi: 10.20956/ijas.v8i2.2518.
- [23] M. A. Budiayanto and M. H. Lubis, "Physical reviews of solar radiation models for estimating global solar radiation in Indonesia," *Energy Reports*, vol. 6, pp. 1206–1211, 2020, doi:10.1016/j.egyr.2020.11.053.
- [24] G. Kim, B. R. Denos, and R. Sterkenburg, "Influence of different piercing methods of abrasive waterjet on delamination of fiber reinforced composite laminate," *Compos. Struct.*, vol. 240, no. August 2019, p. 112065, 2020, doi: 10.1016/j.compstruct.2020.112065.
- [25] D. Qin and C. Chen, "Research on the mechanical property and failure mechanism of the dieless clinched joints of various aluminum alloys," *Eng. Fail. Anal.*, vol. 137, no. April, p. 106384, 2022, doi:10.1016/j.engfailanal.2022.106384.
- [26] V. Naranje and S. Kumar, "A knowledge based system for automated design of deep drawing die for axisymmetric parts," *Expert Syst. Appl.*, vol. 41, no. 4 PART 1, pp. 1419–1431, 2014, doi:10.1016/j.eswa.2013.08.041.
- [27] L. Anggraini, J. Ginting, T. Nola, and K. Takagi, "Efficiency enhancement of die design for G2R-1A relay terminal using progressive tool," *Mater. Today Proc.*, no. xxxx, pp. 1–7, 2023, doi:10.1016/j.matpr.2023.05.623.
- [28] X. Ran, C. Chen, H. Zhang, and Y. Ouyang, "Investigation of the clinching process with rectangle punch," *Thin-Walled Struct.*, vol. 166, no. June, p. 108034, 2021, doi: 10.1016/j.tws.2021.108034.
- [29] Y. Zheng, W. Yuan, X. Liang, and G. Wang, "Surface tension effect on the sliding inception between an elastic sphere and a rigid flat," *Mech. Mater.*, vol. 174, no. September, p. 104477, 2022, doi:10.1016/j.mechmat.2022.104477.
- [30] F. Kappe, C. Zirngibl, B. Schleich, M. Bobbert, S. Wartzack, and G. Meschut, "Determining the influence of different process parameters on the versatile self-piercing riveting process using numerical methods," *J. Manuf. Process.*, vol. 84, no. November, pp. 1438–1448, 2022, doi: 10.1016/j.jmapro.2022.11.019.
- [31] R. F. Liu and J. C. Wang, "Application of finite element method to effect of weld overlay residual stress on probability of piping failure," *Int. J. Press. Vessel. Pip.*, vol. 200, no. September, p. 104812, 2022, doi: 10.1016/j.ijpvp.2022.104812.
- [32] N. Karathanasopoulos, K. S. Pandya, and D. Mohr, "An experimental and numerical investigation of the role of rivet and die design on the self-piercing riveting joint characteristics of aluminum and steel sheets," *J. Manuf. Process.*, vol. 69, no. June, pp. 290–302, 2021, doi:10.1016/j.jmapro.2021.07.049.
- [33] L. Giorleo and E. Ceretti, "Deep drawing punches produced using fused filament fabrication technology: Performance evaluation," *J. Manuf. Process.*, vol. 84, no. March, pp. 1–9, 2022, doi:10.1016/j.jmapro.2022.09.054.
- [34] R. J. Lancaster, S. P. Jeffs, B. J. Haigh, and N. C. Barnard, "Derivation of material properties using small punch and shear punch test methods," *Mater. Des.*, vol. 215, p. 110473, 2022, doi:10.1016/j.matdes.2022.110473.
- [35] B. Isufi, I. Cismasiu, R. Marreiros, A. Pinho Ramos, and V. Lúcio, "Role of punching shear reinforcement in the seismic performance of flat slab frames," *Eng. Struct.*, vol. 207, no. September 2019, 2020, doi: 10.1016/j.engstruct.2020.110238.