













- Conference Series: Materials Science and Engineering, IOP Publishing Ltd, Sep. 2020. doi: 10.1088/1757-899X/935/1/012044.
- [4] H. Purnomo, P. Guizol, and D. R. Muhtaman, "Governing the teak furniture business: A global value chain system dynamic modelling approach," *Environmental Modelling and Software*, vol. 24, no. 12, pp. 1391–1401, Dec. 2009, doi: 10.1016/j.envsoft.2008.04.012.
- [5] J. A. Munib, B. Sudardi, T. S. Pitana, R. Widayat, and D. T. Ardianto, "Buto character developing with utilization of firewood waste to eco-friendly eco-artworks," in *IOP Conference Series: Earth and Environmental Science*, IOP Publishing Ltd, Nov. 2021. doi:10.1088/1755-1315/905/1/012013.
- [6] "Utilization of White Teak Sawdust Waste (Gmelina Arborea Roxb.) as Biodegradable Plastic," *Adv Environ Biol*, 2020, doi: 10.22587/aeb.2020.14.3.2.
- [7] J. Zhang, L. Qu, Z. Wang, Z. Zhao, Z. He, and S. Yi, "Simulation and validation of heat transfer during wood heat treatment process," *Results Phys*, vol. 7, pp. 3806–3812, Jan. 2017, doi:10.1016/j.rinp.2017.09.046.
- [8] A. Vongsvamrungruang, D. Atong, and V. Sricharoenchaikul, "Gasification of Furniture Waste Sawdust in a Cyclone Gasifier," in *IOP Conference Series: Earth and Environmental Science*, Institute of Physics Publishing, May 2018. doi: 10.1088/1755-1315/146/1/012041.
- [9] Y. Wang and J. J. Wu, "Thermochemical conversion of biomass: Potential future prospects," *Renewable and Sustainable Energy Reviews*, vol. 187, Elsevier Ltd, Nov. 01, 2023. doi:10.1016/j.rser.2023.113754.
- [10] S. K. Sansaniwal, K. Pal, M. A. Rosen, and S. K. Tyagi, "Recent advances in the development of biomass gasification technology: A comprehensive review," *Renewable and Sustainable Energy Reviews*, vol. 72, Elsevier Ltd, pp. 363–384, 2017. doi:10.1016/j.rser.2017.01.038.
- [11] S. Mishra and R. K. Upadhyay, "Review on biomass gasification: Gasifiers, gasifying mediums, and operational parameters," *Mater Sci Energy Technol*, vol. 4, pp. 329–340, Jan. 2021, doi:10.1016/j.mset.2021.08.009.
- [12] Maryudi, A. Aktawan, Sunardi, K. Indarsi, and E. S. Handayani, "Biomass Gasification of Sengon Sawdust to Produce Gas Fuel," in *IOP Conference Series: Materials Science and Engineering*, Institute of Physics Publishing, May 2020. doi: 10.1088/1757-899X/821/1/012010.
- [13] A. Trada, A. Chaudhary, D. Patel, and D. S. Upadhyay, "An alternative fuel production from sawdust through batch-type pyrolysis reactor: Fuel properties and thermodynamic analysis," *Process Safety and Environmental Protection*, vol. 167, pp. 332–342, Nov. 2022, doi:10.1016/j.psep.2022.09.023.
- [14] P. Kumar, P. Kumar, P. V. C. Rao, N. V. Choudary, and G. Sriganesh, "Saw dust pyrolysis: Effect of temperature and catalysts," *Fuel*, vol. 199, pp. 339–345, 2017, doi: 10.1016/j.fuel.2017.02.099.
- [15] Y. Jiang *et al.*, "Influence of torrefaction with microwave and furnace heating on pyrolysis of poplar sawdust," *Fuel Processing Technology*, vol. 245, Jun. 2023, doi: 10.1016/j.fuproc.2023.107696.
- [16] N. Couto, A. Rouboa, V. Silva, E. Monteiro, and K. Bouziane, "Influence of the biomass gasification processes on the final composition of syngas," in *Energy Procedia*, Elsevier Ltd, 2013, pp. 596–606. doi: 10.1016/j.egypro.2013.07.068.
- [17] X. Hu and M. Gholizadeh, "Biomass pyrolysis: A review of the process development and challenges from initial researches up to the commercialisation stage," *Journal of Energy Chemistry*, vol. 39, Elsevier B.V., pp. 109–143, Dec. 01, 2019. doi:10.1016/j.jechem.2019.01.024.
- [18] A. K. Varma, L. S. Thakur, R. Shankar, and P. Mondal, "Pyrolysis of wood sawdust: Effects of process parameters on products yield and characterization of products," *Waste Management*, vol. 89, pp. 224–235, Apr. 2019, doi: 10.1016/j.wasman.2019.04.016.
- [19] E. Salehi, J. Abedi, and T. Harding, "Bio-oil from sawdust: Effect of operating parameters on the yield and quality of pyrolysis products," *Energy and Fuels*, vol. 25, no. 9, pp. 4145–4154, Sep. 2011, doi:10.1021/ef200688y.
- [20] P. Comsawang, S. Nanetoe, and N. Soponpongpiat, "Co-firing of sawdust and liquid petroleum gas in the application of a modified rocket stove," *Processes*, vol. 8, no. 1, Jan. 2020, doi:10.3390/pr8010112.
- [21] W. Lan, H. Ding, X. Jin, D. Yin, Y. Wang, and J. Ji, "Catalytic biomass gasification of sawdust: integrated experiment investigation with process modeling and analysis," *International Journal of Low-Carbon Technologies*, vol. 17, pp. 482–487, 2022, doi: 10.1093/ijlct/ctac022.
- [22] J. Kristanto *et al.*, "Kinetic Study on The Slow Pyrolysis of Isolated Cellulose and Lignin from Teak Sawdust," *Thermochim Acta*, vol. 711, May 2022, doi: 10.1016/j.tca.2022.179202.
- [23] W. Wagiran *et al.*, "Temperature Distribution in bio stove using Saw Dust: An integrated project-based learning," *Indonesian Journal of Science and Technology*, vol. 8, no. 1, pp. 127–140, 2023, doi: 10.17509/ijost.v8i1.53476.
- [24] Mujiyono *et al.*, "Experimental study on integrated biomass pyrolysis and gasification process from teak wood waste: Preliminary," in *Journal of Physics: Conference Series*, IOP Publishing Ltd, Dec. 2020. doi: 10.1088/1742-6596/1700/1/012005.
- [25] B. Bučar and A. Straže, "Determination of the thermal conductivity of wood by the hot plate method: The influence of morphological properties of fir wood (*Abies alba* Mill.) to the contact thermal resistance," *Holzforschung*, vol. 62, no. 3, pp. 362–367, May 2008, doi: 10.1515/HF.2008.021.
- [26] K. Maeda, Y. Tsunetsugu, K. Miyamoto, and T. Shibusawa, "Thermal properties of wood measured by the hot-disk method: comparison with thermal properties measured by the steady-state method," *Journal of Wood Science*, vol. 67, no. 1, Dec. 2021, doi: 10.1186/s10086-021-01951-1.
- [27] X. Shi, F. Ronsse, and J. G. Pieters, "Finite element modeling of intraparticle heterogeneous tar conversion during pyrolysis of woody biomass particles," *Fuel Processing Technology*, vol. 148, pp. 302–316, 2016, doi: 10.1016/j.fuproc.2016.03.010.
- [28] W. Wijayanti, Musyaroh, M. N. Sasongko, R. Kusumastuti, and Sasmoko, "Modelling analysis of pyrolysis process with thermal effects by using Comsol Multiphysics," *Case Studies in Thermal Engineering*, vol. 28, Dec. 2021, doi: 10.1016/j.csite.2021.101625.
- [29] C. A. Mgbemene, E. T. Akinlabi, and O. M. Ikumapayi, "Dataset showing thermal conductivity of South-Eastern Nigerian kaolinite clay admixtures with sawdust and iron filings for fired-bricks production," *Data Brief*, vol. 27, Dec. 2019, doi: 10.1016/j.dib.2019.104708.
- [30] M. Charai, H. Sghiouri, A. Mezrab, M. Karkri, K. Elhammouti, and H. Nasri, "Thermal performance and characterization of a sawdust-clay composite material," in *Procedia Manufacturing*, Elsevier B.V., 2020, pp. 690–697. doi: 10.1016/j.promfg.2020.03.098.
- [31] J. Suresh Goud *et al.*, "Heat transfer analysis in a longitudinal porous trapezoidal fin by non-Fourier heat conduction model: An application of artificial neural network with Levenberg–Marquardt approach," *Case Studies in Thermal Engineering*, vol. 49, Sep. 2023, doi:10.1016/j.csite.2023.103265.
- [32] A. Khosravirad and M. B. Ayani, "Comparative analysis of thermal damage to laser-irradiated breast tumor based on Fourier conduction and non-Fourier heat conduction models: A numerical study," *International Communications in Heat and Mass Transfer*, vol. 145, Jun. 2023, doi: 10.1016/j.icheatmasstransfer.2023.106837.
- [33] H. Dai and R. Wang, "Methods for Measuring Thermal Conductivity of Two-Dimensional Materials: A Review," *Nanomaterials*, vol. 12, no. 4, MDPI, Feb. 01, 2022. doi: 10.3390/nano12040589.